



CCITICO PRO PLUS

delivers temps up to 120°C (250°F) at the gun tip. With validations on other microorganisms, the growing list of public information points to the coronavirus being deactivated when being exposed to moisture and temperatures over 80°C (175°F).

Delivering constant all-day steam with no recharge down-time, the **CONTICO** features a large onboard, 1.32 gal detergent tank and 1.32 gal water tank with direct connect continuous water supply system. With its narrow profile, the **CONTICO** is perfect for less accessible areas without 3 phase power. You can even fine tune the moisture and steam jet for precision sanitization.

The compact, cart-style design is perfect for tools and accessories, while the 6 metre hose and 10 metre power cord provide over 52' of range!

A DRY VAPOR STEAMER & VACUUM EXTRACTOR IN ONE!



For more information Call 844 US-STEAM



*Requires 230V 15 amps. Or use with a transformer supported by 2 x 110V circuits

CONTIGO PRO PLUS STEAMER



Pro PLUS Accessory Bundle (included)

QTY	Description
1	Steam & Vacuum Hose 19.6' (6m)
1	5" lance with nozzle (for use with brushes)
1	Triangle brush Polyester brush 1" 65mm
2	Triangle bristle frame for brush
5	Cloth for triangle brush
1	Heavy duty transparent steam vacuum nozzle
1	Steam and vacuum nozzle 6"
1	Window cleaning frame for 6" nozzle
1	Hard surface cleaning frame for 6" nozzle
2	Polyester brush 2.5"
2	Polyester brush 1"
2	Horsehair brush 1"
2	Steam Vacuum Extension Lance, 37"
1	Steam Vacuum Floor Cleaning Head
1	Carpet Frame for Steam Vacuum Floor Cleaning Head
1	Steam Squeegee, 10" Wide with Short Extension
1	Suction Nozzle w/Squeegee, 4"
1	Suction Nozzle, 2"
2	Polyester Brush, 1.5" - Black
2	Stainless Steel Brush, 1.5"
2	Brass Brush, 1.5"







Product Specifications

Electric Power Supply	208~240V, 60Hz
Max output	3350 watts
Heater max	3300 watts
Vacuum motor max	1400 watts
Operating pressure	116 psi (8 bar)
Production Rate	12.5 lbs/hr (5.7 kg/hr)
Max pressure	160 psi (11 bar)
Steam Hose	19.6' (6 m)
Power Cord	32.8' (10 m)
Boiler capacity	0.85 gal (3.2 l)
Water tank	1.32 gal (5 l) + direct connect
Detergent tank	1.32 gal (5 l)
Preheating Time	6 mins
Recovery tank	3.5 gal (13 l)
Boiler material	304 stainless steel
Weight	70.5lbs (32kg)
Dimensions	29x19x41" (745x480x1040mm)